# NSN 5320-01-527-1327

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-527-1327



#### **Thread Class:**

3a

## Head Style:

Countersunk w/reverse chamfer

### Head Height:

Between 0.130 inches and 0.140 inches

#### Shank Diameter:

Between 0.2016 inches and 0.2026 inches

#### Shank Style:

Stump

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

#### **Collar Outside Diameter:**

Between 0.622 inches and 0.628 inches

#### **Collarheight:**

Between 0.724 inches and 0.744 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Collar Inside Diameter:

Between 0.392 inches and 0.398 inches

#### **End Application:**

Ch-53g-helicopter

### Grip Length:

0.688 inches

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.391 inches

#### **Countersink Angle:**

100.0 degrees

#### Collar Style:

Threaded break off type

#### Material:

Steel body

#### Material Specification:

Mil-s-562 military specification single material response body or mil-s-6049 military specification single material response body

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, ty ii, cl2 federal specification all treatment responses body

#### **Thread Series Designator:**

Unjf

# NSN 5320-01-527-1327

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

# Mil-std (military Standard):

Mil-s-562 spec.

