NSN 5320-01-527-1340

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-1340 **Thread Class:** За **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.077 inches and 0.090 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Collar Outside Diameter:** Between 0.355 inches and 0.365 inches Collarheight: Between 0.427 inches and 0.457 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** 0.255 inches **End Application:** Ch-53g-helicopter **Grip Length:** 0.625 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.266 inches **Countersink Angle:** 100.0 degrees **Collar Style:** Threaded break off type Material: Steel body **Material Specification:** Mil-s-562 military specification single material response body or mil-s-6049 military specification single material response body **Surface Treatment:** Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl2 federal specification all treatment responses body

Thread Series Designator:

Unjf

NSN 5320-01-527-1340

Pin-rivet - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-s-562 spec.