NSN 5320-01-527-1341

Pin-rivet - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5320-01-527-1341

3a
Head Style:
Countersunk w/reverse chamfer
Head Height:
Between 0.077 inches and 0.090 inches
Shank Diameter:
Between 0.2016 inches and 0.2026 inches
Shank Style:
Stump
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Collar Outside Diameter:
Between 0.355 inches and 0.365 inches
Collarheight:
Between 0.427 inches and 0.457 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Collar Inside Diameter:
0.255 inches
End Application:
Ch-53g-helicopter
Grip Length:
0.688 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.266 inches
Countersink Angle:
100.0 degrees
Collar Style:
Threaded break off type
Material:
Steel body
Material Specification:
Mil-s-562 military specification single material response body or mil-s-6049 military specification single material response body
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, ty ii, cl2 federal specification all treatment responses body
Thread Series Designator:
Unjf

NSN 5320-01-527-1341

Pin-rivet - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A528u0

Mil-std (military Standard):

Mil-s-562 spec.

Shelf Life: