## NSN 5320-01-527-1343

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-1343 **Thread Class:** За **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.130 inches and 0.140 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Collar Outside Diameter:** Between 0.622 inches and 0.628 inches Collarheight: Between 0.724 inches and 0.744 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.392 inches and 0.398 inches **End Application:** Ch-53g-helicopter **Grip Length:** 0.438 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.391 inches **Countersink Angle:** 100.0 degrees **Collar Style:** Threaded break off type Material: Steel body **Material Specification:** Mil-s-562 military specification single material response body or mil-s-6049 military specification single material response body **Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416, ty ii, cl2 federal specification all treatment responses body

**Thread Series Designator:** 

Unjf

## NSN 5320-01-527-1343

Pin-rivet - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A528u0

Mil-std (military Standard):

Mil-s-562 spec.

Shelf Life: