

View Online at <https://aerobasegroup.com/nsn/5320-01-527-1684>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.130 inches and 0.140 inches

**Shank Diameter:**

Between 0.389 inches and 0.390 inches

**Shank Style:**

Pin-rivet, tapered, threaded

**Head Major Diameter:**

Between 0.530 inches and 0.565 inches

**Tip Diameter:**

Between 0.364 inches and 0.368 inches

**Collar Outside Diameter:**

Between 0.622 inches and 0.628 inches

**Collarheight:**

Between 0.724 inches and 0.744 inches

**Collar Inside Diameter:**

0.665 inches

**End Application:**

Helicopter ch-53g

**Features Provided:**

Washer

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Shear Strength:**

22700 double pounds per square inch

**Countersink Angle:**

45.0 degrees

**Collar Style:**

Threaded break off type

**Special Features:**

Collar finish cadmium plate per ams-qq-p-416, type i, class 2; grip length in inches 0.6875; aluminum washer anodize per mil-a-8625, dye color blue

**Material:**

Steel body

**Material Specification:**

Mil-s-5000 military specification single material response body

**Surface Treatment:**

Cadmium body

**Surface Treatment Specification:**

Qq-p-416, type i, class 2 federal specification single treatment response body

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.