## NSN 5320-01-527-2373

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-2373 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Gray **Fastener Length:** 0.825 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0104 inches and 0.0199 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches **Collar Outside Diameter:** Between 0.303 inches and 0.307 inches Collarheight: Between 0.437 inches and 0.457 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.192 inches and 0.200 inches **Grip Length:** 0.500 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Collar Style:** Threaded break off type **Special Features:** Supplied w/collar and washer Material:

Steel body **Surface Treatment:** Cadmium body and copper body

## NSN 5320-01-527-2373

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A528u0