

View Online at <https://aerobasegroup.com/nsn/5320-01-527-3266>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Red

**Fastener Length:**

0.575 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.104 inches and 0.119 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**Collar Outside Diameter:**

Between 0.303 inches and 0.307 inches

**Collarheight:**

Between 0.437 inches and 0.457 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Collar Inside Diameter:**

Between 0.192 inches and 0.200 inches

**Grip Length:**

0.250 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

10.0 millimeters

**Countersink Angle:**

Between 90.0 degrees and 100.0 degrees

**Collar Style:**

Threaded break off type

**Special Features:**

Supplied w/collar

**Material:**

Steel body

**Surface Treatment:**

Cadmium body

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0