## NSN 5320-01-527-3266

Pin-rivet - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5320-01-527-3266

Thread Direction:
Right-hand
Identification Code Color:
Red
Fastener Length:
0.575 inches
Head Style:
Countersunk w/reverse chamfer
Head Height:
Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.104 inches and 0.119 inches
Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Collar Outside Diameter:
Between 0.303 inches and 0.307 inches
Collarheight:
Between 0.437 inches and 0.457 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Collar Inside Diameter:
Between 0.192 inches and 0.200 inches
Grip Length:
0.250 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
10.0 millimeters
Countersink Angle:
Between 90.0 degrees and 100.0 degrees
Collar Style:
Threaded break off type
Special Features:
Supplied w/collar

## NSN 5320-01-527-3266

Pin-rivet - Page 2 of 2



Material:
Steel body
Surface Treatment:
Cadmium body
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A528u0