## NSN 5320-01-527-3273

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-3273 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.895 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.077 inches and 0.090 inches Width Between Flats: Between 0.122 inches and 0.142 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches **Collar Outside Diameter:** Between 0.408 inches and 0.412 inches Collarheight: Between 0.532 inches and 0.552 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.252 inches and 0.261 inches **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Countersink Angle:** Between 90.0 degrees and 100.0 degrees Collar Style: Threaded break off type **Special Features:** Supplied w/collar Material:

Stainless steel collar

## NSN 5320-01-527-3273

Pin-rivet - Page 2 of 2



Surface Treatment	Sι
-------------------	----

Cadmium collar

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0