

View Online at <https://aerobasegroup.com/nsn/5320-01-527-3276>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.233 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.197 inches and 0.217 inches

**Shank Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.530 inches and 0.565 inches

**Collar Outside Diameter:**

Between 0.622 inches and 0.628 inches

**Collarheight:**

Between 0.724 inches and 0.744 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Collar Inside Diameter:**

Between 0.376 inches and 0.388 inches

**Grip Length:**

0.688 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.375 inches

**Countersink Angle:**

90.0 degrees

**Collar Style:**

Threaded break off type

**Special Features:**

Supplied w/collar and washer

**Material:**

Steel washer

**Surface Treatment:**

Cadmium collar

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0