NSN 5320-01-527-3281

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-527-3281

Thread Class: 3a **Thread Direction: Right-hand** Fastener Length: 0.637 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.104 inches and 0.119 inches Shank Diameter: Between 0.1885 inches and 0.1895 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.357 inches and 0.377 inches **Collar Outside Diameter:** Between 0.303 inches and 0.307 inches **Collarheight:** Between 0.437 inches and 0.457 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.192 inches and 0.200 inches Grip Length: 0.312 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 10.0 millimeters **Countersink Angle:** Between 90.0 degrees and 100.0 degrees **Collar Style:** Threaded break off type **Special Features:** Supplied w/collar Material: Steel body



NSN 5320-01-527-3281

Pin-rivet - Page 2 of 2

Surface Treatment:

Cadmium body

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

