## NSN 5320-01-527-3285

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-3285 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.312 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.160 inches and 0.180 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6287 inches and 0.6335 inches **Collar Outside Diameter:** Between 0.512 inches and 0.518 inches Collarheight: Between 0.652 inches and 0.672 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.314 inches and 0.325 inches **Grip Length:** 0.812 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 8.0 millimeters **Countersink Angle:** 100.0 degrees **Collar Style:** Threaded break off type **Special Features:** Supplied w/collar and washer Material: Stainless steel collar **Surface Treatment:** 

Cadmium collar

## NSN 5320-01-527-3285

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A528u0