

View Online at <https://aerobasegroup.com/nsn/5320-01-527-3287>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.437 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.326 inches and 0.330 inches

Collar Outside Diameter:

Between 0.283 inches and 0.287 inches

Collarheight:

Between 0.427 inches and 0.447 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Collar Inside Diameter:

Between 0.166 inches and 0.173 inches

Grip Length:

0.125 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

8.0 millimeters

Countersink Angle:

Between 90.0 degrees and 100.0 degrees

Collar Style:

Threaded break off type

Special Features:

Supplied w/collar

Material:

Stainless steel collar

Surface Treatment:

Cadmium collar

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0