## NSN 5320-01-527-3288

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-3288 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.437 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3256 inches and 0.3304 inches **Collar Outside Diameter:** Between 0.283 inches and 0.287 inches Collarheight: Between 0.427 inches and 0.447 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.166 inches and 0.173 inches **Grip Length:** 0.125 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 8.0 millimeters **Countersink Angle:** 

100.0 degrees **Collar Style:** Threaded break off type **Special Features:** Supplied w/collar Material: Stainless steel collar **Surface Treatment:** Cadmium collar

## NSN 5320-01-527-3288

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0