

View Online at <https://aerobasegroup.com/nsn/5320-01-527-3290>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.562 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.104 inches and 0.119 inches

**Shank Diameter:**

Between 0.1625 inches and 0.1635 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.3256 inches and 0.3304 inches

**Collar Outside Diameter:**

Between 0.283 inches and 0.287 inches

**Collarheight:**

Between 0.427 inches and 0.447 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Collar Inside Diameter:**

Between 0.166 inches and 0.173 inches

**Grip Length:**

0.250 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

8.0 millimeters

**Countersink Angle:**

100.0 degrees

**Collar Style:**

Threaded break off type

**Special Features:**

Supplied w/collar

**Material:**

Stainless steel collar

**Surface Treatment:**

Cadmium collar

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0