

View Online at <https://aerobasegroup.com/nsn/5320-01-527-3944>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Flush countersunk

**Head Height:**

Between 0.073 inches and 0.075 inches

**Shank Diameter:**

Between 0.201 inches and 0.202 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

Between 0.376 inches and 0.381 inches

**Tip Diameter:**

Between 0.181 inches and 0.184 inches

**Collar Outside Diameter:**

Between 0.303 inches and 0.307 inches

**Collarheight:**

Between 0.437 inches and 0.457 inches

**Collar Inside Diameter:**

0.340 inches

**End Application:**

Helicopter ch-53g

**Shear Strength:**

16000 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Collar Style:**

Threaded break off type

**Material:**

Steel body

**Material Specification:**

Mil-s-5000 military specification single material response body

**Surface Treatment:**

Cadmium body

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response body

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.