## NSN 5320-01-527-5143

Pin-rivet - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5320-01-527-5143

3a
Thread Direction:
Right-hand
Identification Code Color:
Gray
Fastener Length:
0.700 inches
Head Style:
Countersunk w/reverse chamfer
Head Height:
Between 0.045 inches and 0.047 inches
Width Between Flats:
Between 0.104 inches and 0.119 inches
Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Head Major Diameter:
Between 0.297 inches and 0.302 inches
Collar Outside Diameter:
Between 0.303 inches and 0.307 inches
Collarheight:
Between 0.437 inches and 0.457 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Collar Inside Diameter:
Between 0.192 inches and 0.200 inches
Grip Length:
0.375 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.190 inches
Countersink Angle:
Between 90.0 degrees and 100.0 degrees
Collar Style:
Threaded break off type
Special Features:
Supplied w/collar and washer
Material:
Steel body

## NSN 5320-01-527-5143

Pin-rivet - Page 2 of 2



Surface Treatment	Sι
-------------------	----

Cadmium body

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0