## NSN 5320-01-527-5146

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Thread Direction:** 

Fastener Length:

**Identification Code Color:** 

За

Blue



View Online at https://aerobasegroup.com/nsn/5320-01-527-5146

1.438 inches
Head Style:
Countersunk w/reverse chamfer
Head Height:
Between 0.098 inches and 0.112 inches
Width Between Flats:
Between 0.160 inches and 0.180 inches
Shank Diameter:
Between 0.3110 inches and 0.3120 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.472 inches and 0.502 inches
Collar Outside Diameter:
Between 0.512 inches and 0.518 inches
Collarheight:
Between 0.652 inches and 0.672 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Collar Inside Diameter:
Between 0.314 inches and 0.325 inches
Grip Length:
0.938 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.312 inches
Countersink Angle:
Between 90.0 degrees and 100.0 degrees
Collar Style:
Threaded break off type
Special Features:
Supplied w/collar and washer

## NSN 5320-01-527-5146

Pin-rivet - Page 2 of 2



Material:
Stainless steel collar
Surface Treatment:
Cadmium collar
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A528u0