

View Online at <https://aerobasegroup.com/nsn/5320-01-527-5147>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Blue

**Fastener Length:**

0.938 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.098 inches and 0.122 inches

**Width Between Flats:**

Between 0.160 inches and 0.180 inches

**Shank Diameter:**

Between 0.3110 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.472 inches and 0.502 inches

**Collar Outside Diameter:**

Between 0.512 inches and 0.518 inches

**Collarheight:**

Between 0.652 inches and 0.672 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Collar Inside Diameter:**

Between 0.314 inches and 0.325 inches

**Grip Length:**

0.438 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.312 inches

**Countersink Angle:**

Between 90.0 degrees and 100.0 degrees

**Collar Style:**

Threaded break off type

**Special Features:**

Supplied w/collar and washer

**Material:**

Stainless steel collar

**Surface Treatment:**

Cadmium collar

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0