## NSN 5320-01-527-5152

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Thread Direction:** 

Fastener Length:

**Identification Code Color:** 

За

Blue



View Online at https://aerobasegroup.com/nsn/5320-01-527-5152

0.833 inches
Head Style:
Countersunk w/reverse chamfer
Head Height:
Between 0.077 inches and 0.090 inches
Width Between Flats:
Between 0.122 inches and 0.142 inches
Shank Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.415 inches and 0.440 inches
Collar Outside Diameter:
Between 0.408 inches and 0.412 inches
Collarheight:
Between 0.532 inches and 0.552 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Collar Inside Diameter:
Between 0.252 inches and 0.261 inches
Grip Length:
0.438 inches
Thready Qty Per Inch (tpi):
(1)
32
32
32 Min. Tensile Strength (psi):
32  Min. Tensile Strength (psi): 160000 pounds per square inch
32  Min. Tensile Strength (psi): 160000 pounds per square inch  Thread Size:
32 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.164 inches
32 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.164 inches Countersink Angle:
Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.164 inches Countersink Angle: Between 90.0 degrees and 100.0 degrees
Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.164 inches Countersink Angle: Between 90.0 degrees and 100.0 degrees Collar Style:

## NSN 5320-01-527-5152

Pin-rivet - Page 2 of 2



Material:
Stainless steel collar
Surface Treatment:
Cadmium collar
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A528u0