
NSN 5320-01-527-5154

Pin-rivet - Page 1 of 2



Thread Class: 3a **Thread Direction: Right-hand** Identification Code Color: Blue **Fastener Length:** 0.707 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.077 inches and 0.090 inches Width Between Flats: Between 0.122 inches and 0.142 inches Shank Diameter: Between 0.2485 inches and 0.2495 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.415 inches and 0.440 inches **Collar Outside Diameter:** Between 0.408 inches and 0.412 inches **Collarheight:** Between 0.532 inches and 0.552 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.252 inches and 0.261 inches Grip Length: 0.312 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.164 inches **Countersink Angle:** Between 90.0 degrees and 100.0 degrees **Collar Style:** Threaded break off type **Special Features:**

Supplied w/collar and washer



NSN 5320-01-527-5154

Pin-rivet - Page 2 of 2

Material:

Stainless steel collar

Surface Treatment:

Cadmium collar

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

