## NSN 5320-01-527-5156

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-5156 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.013 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Collar Outside Diameter:** Between 0.303 inches and 0.307 inches Collarheight: Between 0.437 inches and 0.457 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.192 inches and 0.200 inches **Grip Length:** 0.688 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.375 inches **Countersink Angle:** 

Between 90.0 degrees and 100.0 degrees

Collar Style:

Threaded break off type

Special Features:

Material:

Supplied w/collar

Stainless steel collar

## NSN 5320-01-527-5156

Pin-rivet - Page 2 of 2



O	·	<b>T</b>	4	
SHILL	ace	Trea	tme	nt.

Cadmium collar

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0