NSN 5320-01-527-5158

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5320-01-527-5158

| Identification Code Color: |
|---|
| Blue |
| Fastener Length: |
| 0.450 inches |
| Head Style: |
| Flush countersunk |
| Width Between Flats: |
| Between 0.104 inches and 0.119 inches |
| Shank Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.376 inches and 0.381 inches |
| Collar Outside Diameter: |
| Between 0.303 inches and 0.307 inches |
| Collarheight: |
| Between 0.437 inches and 0.457 inches |
| Lubrication: |
| Cetyl alcohol, specification 305, hi-shear corp |
| Collar Inside Diameter: |
| Between 0.192 inches and 0.200 inches |
| Grip Length: |
| 0.125 inches |
| Features Provided: |
| Washer |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Thread Size: |
| 0.190 inches |
| Countersink Angle: |
| Between 90.0 degrees and 100.0 degrees |
| Collar Style: |
| Threaded break off type |
| Special Features: |
| Supplied w/collar and washer |

NSN 5320-01-527-5158

Pin-rivet - Page 2 of 2



| Material: |
|---------------------------|
| Stainless steel collar |
| Surface Treatment: |
| Cadmium collar |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A528u0