NSN 5320-01-527-5234

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-527-5234

| Fastener Length: |
|---|
| Between 0.490 inches and 0.510 inches |
| Head Style: |
| Undersized oval countersunk |
| Head Height: |
| Between 0.004 inches and 0.006 inches |
| Shank Diameter: |
| Between 0.249 inches and 0.252 inches |
| Shank Style: |
| Straight w/radius chamfered tip |
| Head Major Diameter: |
| 0.3948 inches |
| Head Minor Diameter: |
| Between 0.316 inches and 0.326 inches |
| Countersink Height: |
| 0.060 inches |
| End Application: |
| F-15 aircraft |
| Shear Strength: |
| 41000 single pounds per square inch |
| Countersink Angle: |
| Between 99.5 degrees and 100.5 degrees |
| Material: |
| Aluminum alloy |
| Material Specification: |
| Qq-a-430, alloy 7050, t73 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 type ii, class 1.Mil-a-8625 type ii, class 1clear military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |