## NSN 5320-01-527-9450

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-9450 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.700 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2021 inches and 0.2028 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.296 inches and 0.315 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.375 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 2500 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 6130 double pounds per square inch **Special Features:** Styll without countersunk Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-527-9450

Pin-rivet - Page 2 of 2



Dem			

Yes - demil/mli

Fiig:

A528u0