# NSN 5320-01-529-5097

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-529-5097

## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.457 inches

### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.094 inches and 0.096 inches

#### Shank Diameter:

0.249 inches

Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.389 inches and 0.394 inches

#### Lubrication:

Dry film and solid film

#### End Application:

F/a-18 hornet

### Grip Length:

Between 1.057 inches and 1.067 inches

#### Thready Qty Per Inch (tpi):

28

#### **Thread Size:**

0.250 inches

#### **Countersink Angle:**

100.0 degrees

#### **Product Name:**

Pin-rivet, threaded, shear, 100 degree c'sunk head, hex point drive

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams-4928 assn standard single material response

### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-529-5097

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

