# NSN 5320-01-529-7645

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-529-7645



# Thread Class:

3a

Thread Direction:

**Right-hand** 

# Fastener Length:

Between 1.248 inches and 1.268 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

0.6335 inches

# End Application:

F/22a raptor

# Grip Length:

Between 0.807 inches and 0.817 inches

# Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

12300 pounds per square inch

# Thread Size:

0.3125 inches

# Shear Strength:

19160 double pounds per square inch

# **Countersink Angle:**

Between 99.30 degrees and 100.30 degrees

# **Product Name:**

Eddie bolt 2 pin

#### **Special Features:**

B" indicates crosslock recess

# Material:

Nickel alloy 718

# **Material Specification:**

Ams 5662 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

# NSN 5320-01-529-7645

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

