

View Online at <https://aerobasegroup.com/nsn/5320-01-529-7645>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.248 inches and 1.268 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.6335 inches

End Application:

F/22a raptor

Grip Length:

Between 0.807 inches and 0.817 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

12300 pounds per square inch

Thread Size:

0.3125 inches

Shear Strength:

19160 double pounds per square inch

Countersink Angle:

Between 99.30 degrees and 100.30 degrees

Product Name:

Eddie bolt 2 pin

Special Features:

B" indicates crosslock recess

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0