NSN 5320-01-529-7646

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-529-7646

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.715 inches and 0.735 inches
Head Style:
Straight pan
Head Height:
Between 0.059 inches and 0.069 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Head Major Diameter:
Between 0.387 inches and 0.412 inches
End Application:
F/22a raptor
Grip Length:
Between 0.370 inches and 0.380 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 28
28
28 Min. Tensile Strength (psi):
28 Min. Tensile Strength (psi): 4300 pounds per square inch
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size:
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength:
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name:
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name: Eddie bolt, 2pin
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name: Eddie bolt, 2pin Special Features:
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name: Eddie bolt, 2pin Special Features: S" indicates spline lock recess
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name: Eddie bolt, 2pin Special Features: S" indicates spline lock recess Material:
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name: Eddie bolt, 2pin Special Features: S" indicates spline lock recess Material: Titanium alloy uns r56400
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name: Eddie bolt, 2pin Special Features: S" indicates spline lock recess Material: Titanium alloy uns r56400 Material Specification:
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name: Eddie bolt, 2pin Special Features: S" indicates spline lock recess Material: Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name: Eddie bolt, 2pin Special Features: S" indicates spline lock recess Material: Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment:
Min. Tensile Strength (psi): 4300 pounds per square inch Thread Size: 0.2500 inches Shear Strength: 9300 double pounds per square inch Product Name: Eddie bolt, 2pin Special Features: S" indicates spline lock recess Material: Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Phosphate

Unjf

NSN 5320-01-529-7646

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0