

View Online at <https://aerobasegroup.com/nsn/5320-01-529-7646>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.715 inches and 0.735 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.059 inches and 0.069 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Head Major Diameter:**

Between 0.387 inches and 0.412 inches

**End Application:**

F/22a raptor

**Grip Length:**

Between 0.370 inches and 0.380 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

4300 pounds per square inch

**Thread Size:**

0.2500 inches

**Shear Strength:**

9300 double pounds per square inch

**Product Name:**

Eddie bolt, 2pin

**Special Features:**

S" indicates spline lock recess

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Ams 2486 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0