NSN 5320-01-529-7867

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-529-7867 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.525 inches and 0.545 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.311 inches **End Application:** F/22a raptor **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 4010 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees **Product Name:** Eddie bolt, 2 pin **Special Features:** S" indicates spline lock recess Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:**

Phosphate

Surface Treatment Specification:

Ams 2486 assn standard single treatment response

Thread Series Designator:

Unjc

NSN 5320-01-529-7867

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0