NSN 5320-01-529-8022

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-529-8022

Thread Class:
3a
Thread Direction:
Right-hand Footoner Longth:
Fastener Length: Between 0.840 inches and 0.860 inches
Head Style:
Straight pan
Head Height:
Between 0.080 inches and 0.090 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.415 inches and 0.440 inches
End Application:
F/22a raptor
Grip Length:
0.500 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
5820 pounds per square inch
Thread Size:
0.2500 inches
Shear Strength:
9300 double pounds per square inch
Product Name:
Eddiebolt-2pin
Special Features:
S"indicates spline lock recess
Material:
Titanium alloy
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:

Ams 2486 assn standard single treatment response

NSN 5320-01-529-8022

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0