

View Online at <https://aerobasegroup.com/nsn/5320-01-529-8552>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.483 inches and 1.493 inches

Width Between Flats:

Between 0.158 inches and 0.161 inches

Shank Diameter:

Between 0.373 inches and 0.374 inches

Shank Style:

Pin-riquet, straight, threaded

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

1520-01-492-6324

Grip Length:

Between 0.933 inches and 0.943 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

95000 single pounds per square inch

Product Name:

Hi-lok pin protruding tension head titanium 1/16 inch grip variation

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 or ams 4967 assn standard single material response

Surface Treatment:

Aluminum alloy

Surface Treatment Specification:

Hi kote 1, cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0