

View Online at <https://aerobasegroup.com/nsn/5320-01-529-8552>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.483 inches and 1.493 inches

**Width Between Flats:**

Between 0.158 inches and 0.161 inches

**Shank Diameter:**

Between 0.373 inches and 0.374 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

1520-01-492-6324

**Grip Length:**

Between 0.933 inches and 0.943 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

95000 single pounds per square inch

**Product Name:**

Hi-lok pin protruding tension head titanium 1/16 inch grip variation

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 or ams 4967 assn standard single material response

**Surface Treatment:**

Aluminum alloy

**Surface Treatment Specification:**

Hi kote 1, cage 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0