NSN 5320-01-529-9822

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style: Straight pan Head Height:

Thread Direction:

Fastener Length:

Between 0.885 inches and 0.905 inches

Between 0.059 inches and 0.069 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-529-9822

Width Between Flats:
Between 0.122 inches and 0.142 inches
Shank Diameter:
Between 0.264 inches and 0.265 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.387 inches and 0.412 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
End Application:
A-10 aircraft
Grip Length:
Between 0.495 inches and 0.505 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
132000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
14600 double pounds per square inch
Material:
Steel comp h11
Material Specification:
Ams6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams2416 assn standard single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-529-9822

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0