

View Online at <https://aerobasegroup.com/nsn/5320-01-530-1218>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.737 inches and 2.757 inches

Head Style:

Straight pan

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.220 inches and 0.224 inches

Shank Diameter:

Between 0.498 inches and 0.499 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.717 inches and 0.752 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10 aircraft

Grip Length:

Between 2.057 inches and 2.067 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

25600 pounds per square inch

Thread Size:

0.500 inches

Shear Strength:

37300 double pounds per square inch

Product Name:

Hi-lok pin

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Ams 6415 assn standard all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty i, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0