

View Online at <https://aerobasegroup.com/nsn/5320-01-530-1463>

**Thread Class:**

3a

**Fastener Length:**

Between 0.733 inches and 0.753 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.079 inches and 0.080 inches

**Shank Diameter:**

0.189 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.265 inches and 0.272 inches

**Lubrication:**

Cetyl alcohol and dry film

**End Application:**

F/a-18 hornet

**Grip Length:**

Between 0.433 inches and 0.443 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Pin, rivet, fluted

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0