NSN 5320-01-530-1476

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-530-1476 **Thread Class:** За Fastener Length: Between 1.045 inches and 1.065 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** 0.202 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.265 inches and 0.272 inches Lubrication: Cetyl alcohol and dry film **End Application:** F/a-18 hornet **Grip Length:** Between 0.745 inches and 0.755 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Pin, rivet, fluted Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-530-1476

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0