NSN 5320-01-530-1559

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style: Straight pan Head Height:

Thread Direction:

Fastener Length:

Between 0.982 inches and 1.002 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-530-1559

Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
End Application:
F/22a raptor
Grip Length:
Between 0.683 inches and 0.693 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
4350 pounds per square inch
Thread Size:
0.1900 inches
Shear Strength:
7060 double pounds per square inch
Product Name:
Eddiebolt-2pin
Special Features:
S" indicates spline lock recess
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal standard single treatment response

NSN 5320-01-530-1559

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0