

View Online at <https://aerobasegroup.com/nsn/5320-01-530-1559>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.982 inches and 1.002 inches

Head Style:

Straight pan

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

End Application:

F/22a raptor

Grip Length:

Between 0.683 inches and 0.693 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

4350 pounds per square inch

Thread Size:

0.1900 inches

Shear Strength:

7060 double pounds per square inch

Product Name:

Eddiebolt-2pin

Special Features:

S" indicates spline lock recess

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0