## NSN 5320-01-530-1559

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-530-1559



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.982 inches and 1.002 inches

## Head Style:

Straight pan

#### **Head Height:**

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

#### **End Application:**

F/22a raptor

Grip Length:

Between 0.683 inches and 0.693 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

4350 pounds per square inch

## Thread Size:

0.1900 inches

## Shear Strength:

7060 double pounds per square inch

#### **Product Name:**

Eddiebolt-2pin

#### **Special Features:**

S" indicates spline lock recess

#### Material:

Nickel alloy 718

#### **Material Specification:**

Ams 5662 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

# NSN 5320-01-530-1559

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

