NSN 5320-01-530-2669

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

0.818 inches
Head Style:
Straight pan
Head Height:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5320-01-530-2669

Between 0.068 inches and 0.080 inches
Shank Diameter:
0.320 inches
Shank Style:
Pin rivet, tapered single groove, type 1 end
Head Major Diameter:
Between 0.475 inches and 0.487 inches
Tip Diameter:
0.312 inches
Lubrication:
Dry film and cetyl alcohol
End Application:
F-15 aircraft
Grip Length:
Between 0.427 inches and 0.443 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
125000 single pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-530-2669

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0