

View Online at <https://aerobasegroup.com/nsn/5320-01-530-2938>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.965 inches and 0.985 inches

**Head Style:**

Flush countersunk

**Head Height:**

0.108 inches

**Width Between Flats:**

0.132 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.475 inches

**End Application:**

F/22a raptor

**Grip Length:**

Between 0.620 inches and 0.630 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.2500 inches

**Shear Strength:**

9300 double pounds per square inch

**Countersink Angle:**

Between 99.3 degrees and 100.3 degrees

**Product Name:**

Eddie bolt, 2pin

**Special Features:**

S" indicates spline lock recess

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Ams 2486 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0