NSN 5320-01-530-2938

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-530-2938

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| Between 0.965 inches and 0.985 inches |
| Head Style: |
| Flush countersunk |
| Head Height: |
| 0.108 inches |
| Width Between Flats: |
| 0.132 inches |
| Shank Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| 0.475 inches |
| End Application: |
| F/22a raptor |
| Grip Length: |
| Between 0.620 inches and 0.630 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.2500 inches |
| Shear Strength: |
| 9300 double pounds per square inch |
| Countersink Angle: |
| Between 99.3 degrees and 100.3 degrees |
| Product Name: |
| Eddie bolt, 2pin |
| Special Features: |
| S" indicates spline lock recess |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment: |
| Phosphate |
| Surface Treatment Specification: |

Ams 2486 assn standard single treatment response

NSN 5320-01-530-2938

Pin-rivet - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A528u0