NSN 5320-01-531-6597



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-531-6597 **Thread Class:**

За

Thread Direction: Right-hand

Fastener Length:

Between 1.248 inches and 1.268 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.6335 inches

End Application:

F/22 raptor

Grip Length:

Between 0.807 inches and 0.817 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

12300 pounds per square inch

Thread Size:

0.3125 inches

Shear Strength:

19160 double pounds per square inch

Countersink Angle:

Between 99.30 degrees and 100.30 degrees

Product Name:

Eddie-bolt 2 pin

Special Features:

S" indicates spline-lok recess

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

NSN 5320-01-531-6597

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0