NSN 5320-01-531-7563

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style:

Thread Direction:

Fastener Length:

Flush countersunk

Width Between Flats:

Between 0.840 inches and 0.860 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-531-7563

0.132 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
0.358 inches
End Application:
F-22 raptor
Grip Length:
Between 0.495 inches and 0.505 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Shear Strength:
12260 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 100.0 degrees
Product Name:
Eddie-bolt 2 pin
Special Features:
"s" indicates spline-lok recess
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-531-7563

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0