

NSN 5320-01-531-7566 Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-531-7566 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.462 inches and 0.482 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.272 inches **End Application:** F-22 raptor **Grip Length:** Between 0.307 inches and 0.317 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 1730 pounds per square inch **Thread Size:** 0.1640 inches

**Shear Strength:** 

4010 double pounds per square inch

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

**Product Name:** 

Eddie-bolt 2pin

Material:

**Titanium** 

**Material Specification:** 

Ams 4928 assn standard single material response

**Surface Treatment:** 

Phosphate

**Surface Treatment Specification:** 

Ams 2486 assn standard single treatment response

**Thread Series Designator:** 

Unjc

## NSN 5320-01-531-7566

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0