NSN 5320-01-531-9754

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style:

Thread Direction:

Fastener Length:

Between 1.060 inches and 1.080 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-531-9754

Straight pan
Head Height:
Between 0.102 inches and 0.112 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3115 inches and 0.3120 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.475 inches and 0.505 inches
End Application:
F/a-22 raptor
Grip Length:
Between 0.620 inches and 0.630 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
12300 pounds per square inch
Thread Size:
0.3125 inches
Shear Strength:
19160 double pounds per square inch
Product Name:
Eddie-bolt 2pin
Special Features:
S" indicates spline-lok recess
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal standard single treatment response

NSN 5320-01-531-9754

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0