NSN 5320-01-531-9756

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-531-9756



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.732 inches and 0.742 inches

Head Style:

Straight pan

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

0.112 inches

Shank Diameter:

Between 0.2177 inches and 0.2182 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

End Application:

F/a 22 raptor

Grip Length:

Between 0.433 inches and 0.443 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

9400 double pounds per square inch

Special Features:

Y" indicates oversize diameter

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-531-9756

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

