## NSN 5320-01-532-6634

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-532-6634

Fastener Length:
1.000 inches
Head Style:
Straight pan
Head Height:
Between 0.130 inches and 0.140 inches
Shank Diameter:
Between 0.258 inches and 0.260 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.400 inches and 0.432 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.281 inches and 0.345 inches
Min. Tensile Strength (psi):
3650 pounds per square inch
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Shear Strength:
5900 single pounds per square inch
Special Features:
This nsn is like 5320-01-195-3016 except this nsn has frangible type of locking collar or locking collar cap.
Material:
Steel comp 8740 stem
Material Specification:
Qq-w-405 federal specification 1st material response sleeve or mil-s-6758 military specification 2nd material response sleeve
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve
Specification Data:
96906-ms90354 government standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A040a0

## NSN 5320-01-532-6634

Blind Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.